Precision Analysis of Electron Energy Deposition in Detectors Simulated by Geant4

M. Batič, S. Granato, G. Hoff, M.G. Pia, <u>G. Weidenspointner</u>

> 2012 NSS-MIC Anaheim, CA Oct. 29 – Nov. 3, 2012

Why electrons (in) matter

- e⁻ are of fundamental importance for a multipurpose Monte Carlo tool such as Geant4

 most detectors: measured signal is energy deposited by ionization, i.e. energy imparted on e⁻
 many applications: e- are primary particles, or important constituents of a particle cascade
- e⁻ are intrinsically difficult to simulate
 - \circ photons: discrete interactions
 - o electrons: on microscopic level, discrete interactions,
 - but usually a condensed transport scheme is employed to avoid IR divergence
 - ⇒ requires model for multiple scattering (continuous energy loss)
 - ⇒ Geant4: mix of continuous and discrete energy loss

eROSITA





- eROSITA:
 - extended Roentgen Survey with an Imaging Telescope Array
- Iaunch 2014 on Russian-German mission Spectrum-X-gamma
- energy range 200 eV to 10 keV
- first imaging all-sky survey in 2.5 10 keV
 ⇒ observation of 10⁵ clusters of galaxies
 - \Rightarrow structure formation, dark energy, ...
- Seven X-ray telescopes,

each with a pnCCD developed at MPI HLL

- pnCCD calibration
 - \Rightarrow X-ray spectral response of pnCCDs

(external or on-chip optical/UV blocking filter)

Measurement: BESSY II at PTB Berlin – 11 keV photons Simulation: Geant4 version 9.2 p02 + HLLDetSim



good agreement

Measurement: BESSY II at PTB Berlin – 7 keV photons Simulation: Geant4 version 9.2 p02 + HLLDetSim

S. Granato



Measurement: BESSY II at PTB Berlin – 3 keV photons Simulation: Geant4 version 9.2 p02 + HLLDetSim

overall good agreement, but deviations due to low energy e⁻ generated close to volume boundaries (photon absorption length 3 µm)



Measurement: BESSY II at PTB Berlin – 1.848 keV photons Simulation: Geant4 version 9.2 p02 + HLLDetSim

No good agreement, problems due to low energy e⁻ generated close to volume boundaries (photon absorption length < 2 μm)



Measurement: BESSY II at PTB Berlin – 1.825 keV photons Simulation: Geant4 version 9.2 p02 + HLLDetSim

overall good agreement, but deviations due to low energy e⁻ generated close to volume boundaries (photon absorption length < 20 µm)



e⁻ and X-rays at volume boundaries



Photo-electric effect: expected behaviour at volume boundaries

e⁻ and X-rays at volume boundaries



(a) number of energy deposits vs. z-position

(b) deposited energy vs. z-position

Electron energy loss by ionization:

pronounced discontinuities / spikes at volume boundaries

Origin unknown...

(related to multiple scattering algorithm?)

Validation of Geant4 with Sandia electron data

• validation of Geant4 requires adequate experimental data

- to our knowledge: no suitable experimental electron data for energies below 25 keV
- BUT: Sandia National Laboratory precision data for 25 keV 1 MeV e⁻, for various incidence angles and materials

 \Rightarrow reference for validation of electron transport models

- SAND79-0414, Lockwood et al., 1987a
 Calorimetric Measurement of Electron Energy Deposition in Extended Media – Theory vs Experiment
 ⇒ validate energy deposition as a function of depth
- SAND80-1968, Lockwood et al., 1987b
 Electron Energy and Charge Albedos Calorimetric Measurement
 vs Monte Carlo Theory
 - \Rightarrow validate electron backscattering and total energy deposition

Validation of Geant4 with Sandia electron data

- status report
- work is ongoing
- current work based on and extends
 A. Lecher, M.G. Pia and M. Sudhakar, 2009, TNS 56, pp. 398 ff.
 Validation of Geant4 Low Energy Electromagnetic Processes against Precision Measurements of Electron Energy Deposition
- same analysis procedure for consistency

Simulation configuration

- Geometry: as in experiment
- e⁻/γ physics:
 - low energy EEDL/EPDL ("Livermore")
 - low energy Penelope
 - o standard

Multiple scattering models:

- \circ Urban
- o Goudsmit-Saunderson

Secondary e⁻ production threshold:

- o 250 eV (low energy, Penelope)
- o 1 keV (standard)

Step limitation:

- ο 1, 10, 1000 μm
- o no limitation

Geant4 versions (with latest patches)

 $8.1, 9.1, 9.2, 9.3, 9.4, 9.5, 9.6-\beta$



Sandia79:

- calorimeter placed at different depths
- all volumes same material

Sandia80:

single sensitive volume

Validation analysis

• **Compatibility** of simulation with experiment:

 χ^2 test
 χ^2 test case: target material, beam energy, beam incidence angle
 o significance of χ^2 test: α = 0.01

 Efficiency of a Geant4 physics model:

 fraction of test cases in which simulation is compatible with experiment



Significance of difference in accuracy between models or versions:
 o categorical analysis

Total energy deposition

- Single volume of single-element material simplest possible test case!
- Used default settings for all models (Geant4 optimized parameters)



 \Rightarrow highest efficiency (best version): Geant4 9.1

⇒ Geant4 9.4: very poor,

dependence on step limitation...!

Energy deposition profiles

- Layers of single-element material second simplest possible test case!
- Used default settings for all models (Geant4 optimized parameters)
- \Rightarrow Best Geant4 version: 9.1



Energy deposition profiles

• Most accurate Geant4: \circ version 9.1 \circ "Livermore" model • equivalence of Geant4 versions and models: \circ 9.1 and 9.5: p-value = 0.008 \circ "Livermore" and Penelope: p-value = 0.002 0.2

"Livermore" and standard:
 p-value < 0.001

Test case: Carbon, 1 MeV, $\theta = 90^{\circ}$

Note: Geant4 9.6- β similar to 9.5

Conclusions

- Accuracy of e⁻ energy deposition in Geant4 depends on:
 - \circ use case
 - \circ software version
 - \circ physics model
- Best choice for low energy electrons: Geant4 version 9.1 with "Livermore" model
- Final results will be published soon in TNS stay tuned...