### MEETING GSI/INFN

**3D Mechanics** 

### 3D MODEL (1/8 OF THE FULL MODEL)

### LOADSTEPS

		half∆y between collars (μm)	half∆y between yokes (μm)
1	collars under pressure	0	
2	collar pressure release	40	
3	iron yoke under pressure	20	0
4	yoke pressure release	35	200/2
<b>5</b>	cool-down	35	55/2
6	energization	35	40/2

3

NODAL SOLUTION STEP=4 SUB =6 TIME=4 SEQV (AVG) DMX =.803948 SMN =1.108 SMX =257.624

# COLLARS UNDER PRESSURE $(\sigma_{max}=260 \text{ MPa})$

1.108	29.609	58.111	86.613	115.115	143.617	172.118	200.62	229.122

### COLLAR POLES

ANSYS 11.0 PLOT NO. 1

ANSYS 11.0 PLOT NO. 1





### COLLARS UNDER PRESSURE

1.108

 $(\sigma_{max}=260 \text{ MPa}, \text{displacements are } 10 \text{ times amplified})$ 

58.111

86.613

29.609





.315434

27.796

### COLLAR PRESSURE RELEASE

 $(\sigma_{max}=250 \text{ MPa}, \text{displacements are 10} \text{times amplified})$ 

55.276

82.756



### PEAK STRESS IN THE LAST TURN

	σ <sub>max</sub> (MPa)
collars under pressure	257.6
collar pressure release	247.6
iron yoke under pressure	274.1
yoke pressure release	261.3
cool-down	227.6
energization	168.5

8

NODAL SOLUTION STEP=4 SDB =6 TIME=4 SEQV (AVG) DMX =12.001 SMN =.441933 SMX =540.598

441933

60.459

MN

ANSYS 11.0 JUL 2 2009 17:02:30 PLOT NO. 1 NODAL SOLUTION STEP=3 SUB =12 TIME=3 SEQV (AVG) DMX =11.961 SMN =.375705 SMX =520.764

.375705 58.197

116.018

231.659

289.48

173.838

480.58

420.563

360.546

300.528

ANSYS 11.0 JUL 2 2009 16:59:15 PLOT NO. 1

462.943

520.764

### COLLARS UNDER PRESSURE $(\sigma_{max}=540 \text{ MPa})$

240.511 180.494

120.477

COLLAR PRESSURE RELEASE  $(\sigma_{max}=520 \text{ MPa})$ 

### MIDPLANE AVERAGE STRESSES 3D (2D)

	<σ <sub>y</sub> > (MPa)	$<\sigma_{eqv}>$ (MPa)
collars under pressure	-92 (-78)	72 (73)
collar pressure release	-86 (-64)	67 (61)
iron yoke under pressure	-101 (-78)	80 (73)
yoke pressure release	-91 (-68)	72 (64)
cool-down	-53 (-38)	49 (39)
energization	-53 (-43)	47 (42)

10



### AZIMUTHAL STRESS ON COIL END BEFORE COOL DOWN



-100	-88.889	-77.778	-66.667	-55.556	-44.444	-33.333	-22.222	-11.111





MN

# AZIMUTHAL STRESS ON COIL END AFTER COOL DOWN ( $0 \rightarrow -100 \text{ MPa}$ )

-100		277 770		_55 556		22 222		
-100	~~ ~~~	-//.//0	6.6 G.67	-55.550			00.000	-11.111
	-88.889		-66.667		-44.444		-22.222	

ANSYS 11.0 JUL 3 2009 08:52:47 PLOT NO. 1

### SOLUTION 1: TAPERING OF THE COLLAR POLE



5.874	24.399	42.924	61.45	79.975	98.501	117.026	135.551	154.077	' 172

### PEAK STRESS IN THE LAST TURN

	σ <sub>max</sub> (MPa) normal collar pole	σ <sub>max</sub> (MPa) tapered collar pole
collars under pressure	257.6	166.8
collar pressure release	247.6	162.4
iron yoke under pressure	274.1	172.6
yoke pressure release	261.3	169.0
cool-down	227.6	160.6
energization	168.5	83.8

### MIDPLANE AVERAGE STRESSES 3D (2D) WITH TAPERED COLLAR POLE

	$<\sigma_{\rm y}>$ (MPa)	$<\sigma_{eqv}>$ (MPa)
collars under pressure	-78 (-78)	62 (73)
collar pressure release	-72 (-64)	58 (61)
iron yoke under pressure	-86 (-78)	69 (73)
yoke pressure release	-77 (-68)	62 (64)
cool-down	-41 (-38)	41 (39)
energization	-41 (-43)	39 (42)



### SOLUTION 2: MIDPLANE TAPERED SHIM



### AZIMUTHAL STRESS BEFORE COOL DOWN $(0 \rightarrow -100 \text{ MPa})$

NO MIDPLANE TAPERED SHIM WITH MIDPLANE TAPERED SHIM



-100	-88,889	-77.778	-66.667	-55.556	-44.444	-33.333	-22.222	-11.111

### AZIMUTHAL STRESS AFTER COOL DOWN $(0 \rightarrow -100 \text{ MPa})$

### NO MIDPLANE TAPERED SHIM NO MIDPLANE TAPERED SHIM



-100	-88,889	-77.778	-66,667	-55.556	-44.444	-33.333	-22.222	-11.111

### LONGITUDINAL LENGTHENING OF WINDING

	μ <sub>r</sub> =0.5 (mm)	$\mu_{\rm r}$ =0.1 (mm)
collars under pressure	+0.19	+0.28
collar pressure release	+0.18	+0.26
iron yoke under pressure	+0.27	+0.38
yoke pressure release	+0.24	+0.32
cool-down	-1.13	-1.21 J J -0
energization	-1.07	$-1.02 \int \Delta L = 0.$

20

### EFFECT OF LONGITUDINAL PRE-STRESS ON FLANGE AND OUTER SHELL



ANSYS 11.0 OCT 28 2009 14:02:24 PLOT NO. 1

# 3D FINITE ELEMENT MODEL



### WHAT'S THE USE OF PRE-STRESS?

• Pre-stress loads in compression the coil ends, to avoid that they could be loaded in traction once the magnet has been energized

• It is crucial to understand which fraction of the Lorentz forces we have to face

# AXIAL AND LONGITUDINAL PRE-STRESS



 $PS_{Y} > FL_{Y}$ no Y displacement of winding  $FL_{Y}$  partially replaces  $PS_{Y}$ 



### LOADING OF PRE-STRESS



$$\begin{cases} P = k_B x_B = k_S x_S \\ x = x_B + x_S \end{cases} \quad \square \qquad P = \frac{k_B k_S}{k_B + k_S} x$$

Stefania Farinon, November 4th 2009

26

### MAGNET ENERGIZATION



 only a fraction of the Lorentz forces contributes to the stress on the outer shell and flange
 this expression is valid for a

concentrated force

27

### DISTRIBUTED FORCE





$$d(\Delta x) = \frac{F_{dx}}{K_{dx}} = \frac{\int_x^L \frac{F}{L} dx}{\frac{L}{dx}K}$$
$$\Delta x = \int_0^L \left(\frac{1}{LK} \int_x^L \frac{F}{L} dx\right) dx$$
$$= \int_0^L \frac{F}{KL^2} (L-x) dx$$

 $\Delta x$ 

total distributed force: F total elastic constant: K

Stefania Farinon, November 4th 2009

 $\frac{F}{2K}$ 

28

### **REAL DISTRIBUTION**



Stefania Farinon, November 4th 2009

29

### LONGITUDINAL DISPLACEMENTS



effective  $FL_Z = 7.3 \text{ kN}$ 

sliding without friction in the coil ends (250 mm)(AVG)



effective  $\mathrm{FL}_{\mathrm{Z}}\!\!=\!\!28.9~\mathrm{kN}$ 

30

### EFFECT OF GRAVITY DURING TEST AT LASA



31

## **REACTION ON END FLANGES**

### PESI SIS\_300

Descrizione Oggetto	Peso Totale [Kg]
Beam tube	21.2
Avvolgimento superiore	65.0
Avvolgimento inferiore	65.0
Contromassa	7.0
Collar	511.5
Chiavette Collar	4.0
Spine Collar	3.5
Flange di testa collar	5.0
Semigiogo	4280.0
Tubi Gioghi	20.2
Tiranti	29.8
C-clamp Giogo	48.7
Barra d'irrigidimento	26.0
Recooling pipe	14.3
Flangia di testa L.C.	44.7
Flangia di testa L.O.C.	43.9
Guscio Esterno	527.2
Totale	5717

• initial pre-stress:

- P<sub>i</sub>=56.2 kN
- gravity:
  - $P_{up}$ = 29.4 kN =  $P_i$ -54.3% of coil weight
  - $P_{down}$ =78.8 kN =  $P_i$ +45.7% of coil weight

### • Lorentz forces:

- $T_{up}=58.3 \text{ kN} = P_{up} + 28.9 \text{ kN}$
- $T_{down}$ =107.6 kN =  $P_{down}$  + 28.9 kN

total weight: 5668 kg
winding weight: 5050.7 kg

Stefania Farinon, November 4th 2009

32

### VON MISES STRESS PRE-STRESS OF 5.6 kN



33

### VON MISES STRESS PRE-STRESS OF 5.6 kN + GRAVITY



34

### VON MISES STRESS - PRE-STRESS OF 5.6 kN + GRAVITY + LORENTZ FORCES



35